



WALINGA[®]
3510 AGRI-VAC^{INC.}



3510 Agri-Vac



CLEAN UP

- Portable
- Efficient
- Versatile

The **3510 AGRI-VAC**, equipped with a WALINGA #510 blower, can move up to 700 bu/hr (18 tonnes/hr). Weighing less than 900 lb. (410 kg), it can be used in the tightest corners to perform transfer, cleanup or loading operations. The movement of the grain using a cushion of air provides minimum damage and maximum capacity, important for the re-use and re-sale of grain. The 3510 gas/electric model is mounted on a formed steel, three wheeled cart, which makes it very simple to move into the smallest corner of your storage area. Available in 25 hp gas, 10/15/20 hp electric, or with a 3 point hitch, it is the ideal unit for someone who needs a versatile and portable grain handling unit.

SPECIFICATIONS:

	3510G (gasoline)	3510E (electric)	3510 3PH (PTO)
Weight	820 lbs (373 kg)	770 lbs (350 kg)	900 lbs (410 kg)
Height	60 inch (152 cm)	60 inch (152 cm)	60 inch (152 cm)
Width	36 inch (91 cm)	36 inch (91 cm)	47 inch (119 cm)
Length	78 inch (198 cm)	78 inch (198 cm)	78 inch (198 cm)
Wheels	3 pneumatic (1 on swivel)	3 pneumatic (1 on swivel)	mounted on legs
Blower	#510 Walinga blower	#510 Walinga blower	#510 Walinga blower
Airlock	#1210U two piece cast	#1210U two piece cast	#1210U two piece cast
Frame	1 piece formed steel	1 piece formed steel	1 piece formed steel
Motor/Power	25 hp gas (18.4 KW)	10,15 or 20 hp (7.5,11,15 KW)	540 PTO (25 + hp)
Starter	12 volt	"across the line"	not applicable
Receiver	18" dia. x 36" high (46 x 91 cm)	18" dia. x 36" high (46 x 91 cm)	18" dia. x 36" high (46 x 91 cm)
Inlet	4" (100 mm) daffin coupling with plug	4" (100 mm) daffin coupling with plug	4" (100 mm) daffin coupling with plug
Outlet	4" (100 mm) daffin coupling with plug	4" (100 mm) daffin coupling with plug	4" (100 mm) daffin coupling with plug

Due to continuous product development, specifications are subject to change without notice.



BLOWER/AIRLOCK

- 510 positive displacement WALINGA blower
- 12"x10" (31x26 cm) Airlock with rubber tips
- Combination belt/chain drive

OPTIONS

- 24hp Honda
- Stainless steel hoses
- 3" (75 mm) rubber suction hose
- Discharge cyclone
- Remote shut off (gas model only)

ACCESSORIES

- Nozzle:**
- 4" Suction Nozzle
 - 4" (100 mm) with cleanup head
- Hoses:**
- One 4" x 12' (100 mm x 3.65 m) rubber suction hose
 - One 4" x 12' (100 mm x 3.65 m) galvanized discharge hose



3510 G



3510 E



3510 3PH

CAPACITIES:

Model	Product	Barley		Corn		Wheat		Beans	
		Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr
3510 25 hp GAS		700	18	650	17	500	13	450	12
3510 E (20 hp)		700	18	650	17	500	13	450	12
3510 E (15 hp)		550	14	500	13	375	10	350	9
3510 E (10 hp)		400	10	350	9	250	7	225	6
3510 3PH		700	18	650	17	500	13	450	12

*Capacities based on using 12' (3.5 m) long suction line and truck loading kit. Capacity will vary with condition of product.



Head office:
R.R. #5, Guelph, ON.
Canada N1H 6J2
Tel (888) 925-4642
Fax (519) 824-5651

Michigan:
1190 Electric Ave.
Wayland, MI.
USA 49348
Tel (800) 466-1197
Fax (616) 877-3474

Manitoba:
70 3rd Ave. N.E. Box 1790
Carman, Manitoba
Canada ROG OJ0
Tel (204) 745-2951
Fax (204) 745-6309

Saskatchewan:
P.O. Box 849
220 Frontage Rd.
Davidson, Saskatchewan
Canada S0G 1A0
Tel (306) 567-3031
Fax (306) 567-3039

www.walinga.com