



WALINGA®

8614 DLX AGRI-VAC



8614 DLX Agri-Vac



8614

STANDARD ACCESSORIES

- Hydraulic Boom Rotation and lift
- Hose carrier
- 6" (150 mm) cleanup hose package
- Extra-Thick chrome blower
- Precleaner on 8614 DLX
- Dual inlets on 8614 DLX
- Self contained hydraulics on 8614 DLX
- Fully rhino lined receiver tank, boom elbow and boom cyclone.
- Hydraulic-rotating truck loading kit with cyclone
- Two 8" dia. x 12' (203 mm x 3.65 m) stainless steel delivery line
- One 8" (203 mm) dia. suction nozzle
- One 6" dia. x 12' (150 mm x 3.65 m) stainless steel delivery line
- One 6" (150 mm) dia. suction nozzle
- One 6" dia. x 12' (150 mm x 3.65 m) rubber clean-up hose
- One 6" (150 mm) dia. suction nozzle with clean-up attachment
- One 6" to 8" adapter (150 mm-203 mm)

**SPECIFICATIONS FOR:
Walinga Pneumatic Grain Moving Unit
Model 8614 DLX**

| | 8614 DLX |
|------------------|---|
| Height | 134" (343 cm) |
| Width | 101" (259 cm) |
| Length | 172" (442 cm) |
| Weight | 6380 lbs (2900 kg) |
| Discharge Height | 15' maximum (4.57 m) |
| hp required | 200-230 hp |
| PTO speed | 1000 RPM |
| Line size | 6" and 8" (150 mm & 203mm) |
| Tires | Two Large Farm Implement |
| Wheels | 15" (38 cm), 6 stud |
| Blower | Two 614 Walinga Super Chrome, positive displacement blowers |
| Airlock | KICE, 3.2 cubic feet/rev, chrome plated, abrasion resistant adjustable steel tips, hydraulically driven, reverse rotation |
| Drive | Tongue mounted drive shaft with V-type 4 groove sheaves & belts |
| Hydraulics | Self contained hydraulic system |
| Receiver | 37.5" dia. (96 cm) two piece, dual inlet |
| Precleaner | 31.5" dia. (81 cm) |
| Safety | Vacuum/Pressure relief valves |



UNIT SHOWN IN TRANSPORT MODE

| 8614 DLX | | |
|---------------|--------|------------|
| CAPACITY* | Bu/hr* | Tonnes/hr* |
| Corn & Barley | 7000 | 178 |
| Wheat | 6500 | ? |
| Soybeans | 6000 | ? |

Due to continuous product development, specifications are subject to change without notice.

Some items shown may be optional.

*Capacities based on using 12' (3.65 m) suction line and truck loading kit. Capacity will vary with condition of product.



Head Office:
938 Glengarry Cres.
Fergus ON, Canada
N1M 2W7
Tel: (519) 787-8227
Fax: (519) 787-8210

Michigan:
1190 Electric Ave.
Wayland, MI.
USA 49348
Tel (800) 466-1197
Fax (616) 877-3474

Manitoba:
70 3rd Ave. N.E. Box 1790
Carman, Manitoba
Canada R0G 0J0
Tel (204) 745-2951
Fax (204) 745-6309

Saskatchewan:
P.O. Box 849
220 Frontage Rd.
Davidson, Saskatchewan
Canada S0G 1A0
Tel (306) 567-3031
Fax (306) 567-3039

www.walinga.com